








































GUÍA PARA LA SELECCIÓN DE LAS HERRAMIENTAS NEUMÁTICAS

LLAVES DE IMPACTO
















■	CÓDIGO BETA	N °	MATERIAL	 max. Nm	 db (A) LpA	 db (A) LpW	 l/min.	 kg	MECANISMO	 m/s ²
3/8"		1924F	Aluminio	108	93.6	104.6	59	0,5	Doble maza	6.85
3/8"		1924B	Aluminio	353	91	95	80	1,5	Maza individual	7.9
3/8"		1924CD	Composite	410	91.7	102.7	79	1,3	Doble maza	6.2
1/2"		1927AN	Aluminio	244	89.4	100.4	190	2,1	Single hammer	8.63
1/2"		1927G	Aluminio	325	92.2	103.2	113	1,2	Single hammer	9.96
1/2"		1927B	Aluminio	705	98.0	109.0	133	2,1	Maza individual	14.08
1/2"		1927XM	Aluminio	770	102	113	122	1,3	Single hammer	7.5
1/2"		1927CD	Composite	1.020	95.5	106.5	130	2,3	Doble maza	7.2
1/2"		1927P	Composite	1.750	95.1	106.1	290	2,0	Doble maza	6.7
3/4"		1928XM	Aluminio	1.600	91.8	102.8	175	2,9	Doble maza	12.96
3/4"		1928DA	Aluminio	1.695	96	99.5	300	4,3	Doble maza	3.6
3/4"		1928DAL	Aluminio	1.695	96	99.5	300	4,8	Doble maza	3.6
3/4"		1928CD	Composite	1.800	97.5	108.5	215	3,5	Doble maza	11.4
1"		1930CD	Composite	2.445	95.6	97.1	410	7,1	Doble maza	3,6
1"		1930PA	Aluminio	2.445	96.0	97.1	410	9,6	Doble maza	7,2
1"		1930A	Aluminio	2.445	103.3	114.3	460	9,5	Doble maza	67
1"		1930LH	Aluminio	2.441	97.1	108.1	282	7,1	Doble maza	17.4
1"		1930LA	Aluminio	2.445	95.6	97.1	460	10,6	Doble maza	3,6
1"		1930HLA	Aluminio	3.661	99	101	460	16,4	Doble maza	16,4
1 1/2"		1930ZL	Aluminio	4.068	102.4	113.4	480	15	Doble maza	69.6

GUÍA PARA LA SELECCIÓN DE LAS HERRAMIENTAS NEUMÁTICAS

CARRACAS

■	CÓDIGO BETA	N°.	 max. Nm	 db (A) LpA	 db (A) LpW	 l/min.	 kg	 m/s ²
14"		1921B1	24	96	85	90	0,4	2.6
14"		1921M1	27	84	88	96	0,6	1.8
14"		1922P1	68	90.6	101.6	88	0,6	8.61
38"		1921M2	27	84	88	96	0,6	1.8
38"		1922P2	68	90.6	101.6	88	0,6	8.61
12"		1921N3	68	80	87	140	1,2	2.6
12"		1922P3	136	94.9	105.9	113	1,5	18.28

ESMERILADORAS

	CÓDIGO BETA	N°.	POTENCIA	 db (A) LpA	 db (A) LpW	 l/min.	 kg	 m/s ²
		1933	0,20 kW	80.0	87.0	230	0,38	4.53
		1933L	0,20 kW	80.0	87.0	270	0,67	1.15
		1933AN90	0,20 kW	80.0	87.0	230	0,51	1.24
		1933I	0,38 kW	80.0	87.0	260	0,67	4.53
		1933IL	0,38 kW	79.0	97.0	113	1,4	1.6
		1933IH	0,75 kW	88.1	99.1	370	0,8	2.6
		1933ILH	0,75 kW	85.7	96.7	370	1,2	1.4
		1933AN90-H	0,75 kW	85.6	96.6	370	1,1	6.7
		1934MAV	0,04 kW	71	76	115	0,2	2.5
		1934MAV70	0,08 kW	80	87	115	0,2	4